S2770RT/S3370RT/S3970RT

COMPACT ROUGH TERRAIN SCISSOR LIFTS



- Compact diesel rough terrain scissor lifts
- Excellent rough terrain performance
- Roll-out deck extension for extra reach
- Ideal for outdoor work in confined spaces



COMPACT RT SCISSOR LIFTS S2770RT/S3370RT/S3970RT

DIMENSIONS	\$2770RT	\$3370RT	\$3970RT	
Max. working height	33 ft	39 ft	45 ft	
Max. platform height (A)	27 ft	27 ft 33 ft		
Platform size (stowed) (B)	9 ft 8 in x 5 ft 2 in			
Platform size (extended) (C)	13 ft 1 in x 5 ft 2 in			
Extension deck length	4 ft	4 ft	4 ft	
Overall width (D)	5 ft 10 in	5 ft 10 in	5 ft 10 in	
Overall length (E)	11 ft	11 ft	11 ft	
Stowed height (F)	8 ft 7 in	9 ft	9 ft 8 in	
Min. height (guardrails folded)	6 ft	6 ft 6 in	7 ft	
Ground clearance	13 in	13 in	13 in	


PERFORMANCE			
Platform capacity (SWL)	1,250 lbs	1,000 lbs	771 lbs
Max. drive height	27 ft	33 ft	39 ft
Max. wind speed	28 mph	28 mph	28 mph
Max. drive speed (stowed)	2.8 mph	2.8 mph	2.8 mph
Max. drive speed (elevated)	0.3 mph	0.2 mph	0.2 mph
Raise/lower time	26/30 sec	50/60 sec	50/60 sec
Gradeability	35%	35%	35%
Max. stabilizer levelling, front to rear	6°	6°	6°
Max. stabilizer levelling, side to side	10°	10°	10°
Inside turning radius	8 ft 10 in	8 ft 10 in	8 ft 10 in
Outside turning radius	16 ft 3 in	16 ft 3 in	16 ft 3 in
Tires	27 x 10.5 -15, non-marking foam filled		
Controls	proportional joystick		
Drive system	4-wheel drive		


POW	ΕĐ
$\Gamma \cup W$	нν

Kubota D-902 water-cooled diesel 22.5 hp - Tier 4 Final Power source

WEIGHT			
Weight	6,636 lbs	7,980 lbs	8,355 lbs

TURNING RADIUS





STANDARD FEATURES

- 4-wheel drive
- Roll-out deck extension
- 4 hydraulic stabilizers with automatic leveling
- Non-marking foam filled tires
- Proportional controls
- Power line to platform
- Platform overload system
- Drive motion alarm
- Descent alarm
- Fold-down guardrails
- Flashing amber lights (2)
- Oscillating axle
- Hour meter & on-board diagnostics display
- Manual lowering valve
- Dual lanyard attachment points
- 2 year parts & labor, 5 year structural warranty
- ANSI compliant

OPTIONS

- Special paint colors
- Hydraulic generator 110V 2kW
- Dual fuel
- Nylon spreader pads (set of 4)
- Environmental hydraulic oil
- Cold weather package (block heater + battery warm up)
- Turf/Floatation tires (S2770RT & S3370RT only)



St.Joseph, MO 64502-1160, USA

Tel: 1 (785) 989-3000 Toll-free: 1 (800) 255-0317

Fax: 1 (785) 989-3070

Email: sales.usa@snorkellifts.com