S9056RT-HC/S9070RT-HC ULTRA-HIGH CAPACITY ROUGH TERRAIN SCISSOR LIFTS



- Ultra-high capacity, large deck rough terrain scissor lifts
- Excellent rough terrain performance
- Heavy duty design
- Dual powered extension decks
- Ideal for construction applications



ULTRA-HIGH CAPACITY ROUGH TERRAIN SCISSOR LIFTS

DIMENSIONS	\$9056RT-HC*	S9070RT-HC*	
Max. working height	62 ft	76 ft	
Max. platform height (A)	56 ft	70 ft	
Platform size (stowed)	16 ft x 7 ft 6 in		
Platform size (extended)	27 ft x 7 ft 6 in		
Extension deck length	4 ft 6 in	4 ft 6 in	
Overall width (B)	7 ft 6 in	7 ft 6 in	
Overall length (C)	16 ft	16 ft	
Stowed height (D)	10 ft 2 in	11 ft 3 in	
Min. height (guardrails folded)	7 ft	8 ft 5 in	
Ground clearance	14 in	14 in	

PERFORMANCE			
Platform capacity (SWL)	2,500 lbs	2,000 lbs	
Max. drive height	43 ft	43 ft	
Max. wind speed	28 mph	28 mph	
Max. drive speed (stowed)	4.2 mph	4.2 mph	
Max. drive speed (elevated)	0.6 mph	0.6 mph	
Raise/lower time	55/35 sec	70/40 sec	
Gradeability	50%	50%	
Max. stabilizer levelling, front to rear	6°	6°	
Max. stabilizer levelling, side to side	12°	12°	
Inside turning radius	8 ft	8 ft	
Outside turning radius	18 ft 6 in	18 ft 6 in	
Tires	13 x 36 foam filled		
Controls	proportional joystick		
Drive system	4-wheel drive		

POWER

Power source


Kubota diesel

WEIGHT		
Weight	20,000 lbs	25,500 lbs

TURNING RADIUS


ANSI Specification

©Snorkel 2024



S9056RT-HC/ **S9070RT-HC**

D



STANDARD FEATURES

- 4-wheel drive •
- 4 hydraulic stabilizers with automatic levelling •
- Dual powered extension decks
- Proportional controls
- Foam filled tires
- Power line to platform
- Platform overload system
- Drive motion alarm •
- Descent alarm
- Locking, oscillating axle
- Fold-down guardrails •
- Manual lowering valve •
- Flashing amber light (x2) •
- Dual lanyard attachment points •
- Hour meter & on-board diagnostics display •
- 2 year parts & labor, 5 year structural warranty

• ANSI compliant

OPTIONS

- Special paint colors
- Nylon spreader pads (set of 4)
- Environmental hydraulic oil
- Dual fuel
- Non-marking foam filled tires
- Cold weather package (block heater + battery warm up)
- Hydraulic 110V 2kW generator
- 12kW generator package



P.O. Box 1160 St.Joseph, MO 64502-1160, USA Tel: 1 (785) 989-3000 Toll-free: 1 (800) 255-0317 Fax: 1 (785) 989-3070 Email: sales.usa@snorkellifts.com

.com