# **AB60J** ARTICULATING BOOM LIFTS



- Tough & reliable diesel articulating boom lift
- Powerful 4-wheel drive for rough terrain
- Robust, rental-tough design
- Simple to operate and maintain
- Ideal for both maintenance and construction applications



### **ARTICULATING BOOM LIFTS**

DIMENSIONS	AB60J
Max. Working Height	65′ 9″ (20.04m)
Max. Platform Height	59′ 9″ (18.21m)
Max. Horizontal Reach	43′ 1″ (13.13m)
Clearance Height @ Max. Outreach	19' 6" (5.94m)
Platform Size	8' x 3' (2.44m x 0.91m)
Overall Length ( <b>A</b> )	29' 2" (8.89m)
Overall Width ( <b>B</b> )	7′ 11.5″ (2.42m)
Stowed Height ( <b>C</b> )	8′ 3″ (2.51m)
Ground Clearance	12" (305mm)

PERFORMANCE	
Platform Capacity	500 lbs (227kg)
Max. Drive Height	59′ 9″ (18.21m)
Max. Wind Speed	28mph (12.5m/s)
Max. Drive Speed (Stowed)	3.2mph (5.15km/h)
Max. Drive Speed (Elevated)	0.6mph (0.96km/h)
Gradeability	20%
Jib Length	6′ (1.82m)
Jib Arc	75°
Platform Rotation	180°
Superstructure Rotation (Continuous)	360°
Tailswing (Riser-boom Elevated)	0" (0.0m)
Tailswing (Riser-boom Stowed)	60" (1.52m)
Raise / Lower Time	125 / 121 seconds
Tires (Foam-filled lug)	15" x 19.5" (38.1cm x 49.5cm)
Controls	Proportional joystick – drive, lift & rotation
Drive System	4WD

#### POWER

Power Source


WEIGHT


Weight

#### 24,800 lbs (11,249kg)

65hp Kubota V2403 diesel engine

#### WORKING ENVELOPE





AB60J

#### STANDARD FEATURES

- Snorkel Guard<sup>™</sup> secondary guarding system
- Hydraulic platform rotation
- 4-wheel drive
- Proportional drive, lift & swing
- Lanyard attachment points
- Horn
- Foam-filled tires
- Power line to platform
- Tilt alarm & cut out
- Platform overload system
- Drive motion alarm
- Flashing amber strobe
- 2-year parts & labor warranty
- 5-year structural warranty

#### **OPTIONS**

- Airline to platform
- AC generator 110V/2.5kW (single phase)
- Environmental hydraulic oil
- Non-marking tires
- Special paint colors
- Tool tray

## Snorkel

P.O. Box 1160 St. Joseph, MO 64502-1160, USA

Tel: 1 (785) 989-3000

Toll-Free: 1 (800) 255-0317 Email: sales.usa@snorkellifts.com