# **AB80J/AB85J** ARTICULATING BOOM LIFTS



- Tough & reliable diesel articulating boom lift
- Powerful 4-wheel drive for rough terrain
- Robust, rental-tough design
- Simple to operate and maintain
- Ideal for both maintenance and construction applications



## **ARTICULATING BOOM LIFTS**

| DIMENSIONS                       | AB80J                   | AB85J            |
|----------------------------------|-------------------------|------------------|
| Max. Working Height              | 85′ 11″ (26.18m)        | 90' 6" (27.58m)  |
| Max. Platform Height             | 79' 11" (24.35m)        | 84' 6" (25.75m)  |
| Max. Horizontal Reach            | 59' 5" (18.11m)         | 61′ 11″ (18.87m) |
| Clearance Height @ Max. Outreach | 27′ 11″ (5.94m)         |                  |
| Platform Size                    | 8' x 3' (2.44m x 0.91m) |                  |
| Overall Length ( <b>A</b> )      | 41' 3" (12.57m)         | 42' 3" (12.87m)  |
| Overall Width ( <b>B</b> )       | 8′ 6″ (2.59m)           |                  |
| Stowed Height ( <b>C</b> )       | 9' 10" (3.00m)          |                  |
| Ground Clearance                 | 13" (330mm)             |                  |

| PERFORMANCE                 |                             |                  |
|-----------------------------|-----------------------------|------------------|
| Platform Capacity           | 500 lbs (227kg)             |                  |
| Max. Drive Height           | 79' 11" (24.35m)            | 84' 6" (25.75m)  |
| Max. Wind Speed             | 28mph (12.5m/s)             |                  |
| Max. Drive Speed (Stowed)   | 3.0mph (4.83km/h)           |                  |
| Max. Drive Speed (Elevated) | 0.6mph (0.96km/h)           |                  |
| Gradeability                | 30%                         |                  |
| Jib Length                  | 5′ (1.52m)                  | 6' 6" (1.98m)    |
| Jib Arc                     | 140° (+70°/-70°)            | 135° (+70°/-65°) |
| Platform Rotation           | 150°                        |                  |
| Superstructure Rotation     | 360° continuous             |                  |
| Tailswing                   | 35" (0.89m)                 |                  |
| Raise / Lower Time          | 240 / 240 seconds           |                  |
| Tires (Foam-filled)         | 15" x 625 (38.1cm x 97.8cm) |                  |
| Controls                    | Proportional joystick       |                  |
| Drive System                | 4WD                         |                  |

#### POWER

Power Source

65hp Kubota V2403 diesel engine

#### WEIGHT

Weight

36,800 lbs (16,692kg) 38,580 lbs (17,500kg)

### WORKING ENVELOPE



```
AB80J/AB85J
```



#### **STANDARD FEATURES**

- Snorkel Guard<sup>™</sup> secondary guarding system
- Hydraulic platform rotation
- 4-wheel drive
- 4-wheel steer, including crab steer
- Proportional drive, lift & swing, extend & rotate
- Lanyard attachment points
- Horn
- Foam-filled tires
- Power line to platform
- Tilt alarm & cut out
- Platform overload system
- Drive motion alarm
- Flashing amber strobe
- 2-year parts & labor warranty
- 5-year structural warranty

#### **OPTIONS**

- Airline to platform
- AC generator 110V/240V 2.5kW (single phase)
- Environmental hydraulic oil
- Non-marking tires
- PFAS
- Special paint colors
- Tool tray



P.O. Box 1160 St. Joseph, MO 64502-1160, USA Tel: 1 (785) 989-3000 Toll-Free: 1 (800) 255-0317 Email: sales.usa@snorkellifts.com