S6926RTE / S6933RTE NEW

ROUGH-TERRAIN LITHIUM SCISSOR LIFTS





- Powerful electric rough-terrain scissor lifts
- Excellent rough-terrain performance
- Roll-out deck extension
- Ideal for indoor/outdoor work



ROUGH-TERRAIN LITHIUM SCISSOR LIFTS


DIMENSIONS	S6926RTE	S6933RTE
Max. Working Height	32' (9.75m)	39' (11.90m)
Max. Platform Height (A)	26' (7.92m)	33' (10.05m)
Platform Size (Stowed)	147" x 69" (3.70m x 1.75m)	
Platform Size (Extended)	189.4" x 69" (4.81m x 1.75m)	
Deck Extension Length	34" (0.86m)	
Overall Length (B)	12′ 5″ (3.78m)	
Overall Width (C)	5′ 9″ (1.75m)	
Stowed Height (D)	8′ 2″ (2.49m)	8′ 8.3″ (2.65m)
Ground Clearance (Stowed)	10.1" (256mm)	

PERFORMANCE		
Platform Capacity	1,500 lbs (680kg)	1,000 lbs (453kg)
Max. Drive Height	26' (7.92m)	33' (10.05m)
Max. Wind Speed	28 mph (12.5m/s)	
Max. Drive Speed (Stowed)	3.5 mph (5.6m/s)	
Max. Drive Speed (Elevated)	0.38 mph (0.61m/s)	
Gradeability	35%	
Outrigger Leveling (Side-to-side)	11° max.	
Outrigger Leveling (Front-to-back)	6° max.	
Raise/Lower Time	37 / 37 seconds	44 / 40 seconds
Tires (Non-marking foam-filled)	26" x 12" (66.0cm x 30.5cm)	
Controls	Proportional joystick	
Drive System	2WD standard (4WD optional)	
Motor	AC electric motor	


POWER	
Power Source	(6) 48v, 30Ah Li-ion batteries with BMS
Charger	48V pylon charger

WEIGHT		
Weight	9.790 lbs (4.441kg)	11.920 lbs (5.407kg)

TURNING RADIUS



S6926RTE / S6933RTE



STANDARD FEATURES

- (2) 222Ah lithium-ion battery systems
- 2-wheel drive
- Dual-powered deck extension
- Non-marking foam-filled tires
- Proportional controls
- Power line to platform
- Platform overload system
- Drive motion alarm
- Descent alarm
- Fold-down guardrails
- Flashing amber strobes (x2)
- Locking oscillating axle
- Hour meter & on-board diagnostic display
- Manual lowering valve
- Dual lanyard attachment points
- 2,000 charging cycles / 2-year** lithium battery warranty
- 2-year parts & labor warranty
- 5-year structural warranty

OPTIONS

- 4-wheel drive
- Generator set
- Hydraulic stabilizers
- Environmental hydraulic oil
- Special paint colors



P.O. Box 1160

St. Joseph, MO 64502-1160, USA

Tel: 1 (785) 989-3000 Toll-Free: 1 (800) 255-0317

Email: sales.usa@snorkellifts.com