S9056RT-HC/S9070RT-HC LARGE-DECK HIGH-CAPACITY ROUGH-TERRAIN SCISSOR LIFTS



- Ultra-high capacity, large-deck rough-terrain scissor lifts
- Excellent rough-terrain performance
- Dual-powered extension decks
- Ideal for heavy-duty construction applications



LARGE-DECK HIGH-CAPACITY **ROUGH-TERRAIN SCISSOR LIFTS**

DIMENSIONS	S9056RT-HC	S9070RT-HC
Max. Working Height	62' (18.89m)	76' (23.16m)
Max. Platform Height (A)	56' (17.06m)	70' (21.33m)
Platform Size (Stowed)	18' x 7' 4" (5.48m x 2.23m)	
Platform Size (Extended)	27' 4" x 7' 4" (8.33m x 2.23m)	
Deck Extension Length	4′ 8″ (1.42m)	
Overall Length (B)	16' 10" (5.13m)	
Overall Width (C)	7′ 6″ (2.28m)	
Stowed Height (D)	10' 4" (3.15m)	11' 2" (3.40m)
Ground Clearance (Stowed)	8.7" (221mm)	

PERFORMANCE		
Platform Capacity	3,000 lbs (1,361kg)	2,000 lbs (907kg)
Max. Drive Height	56' (17.06m)	70' (21.33m)
Max. Wind Speed	28mph (12.5m/s)	
Max. Drive Speed (Stowed)	4.0mph (6.4m/s)	
Max. Drive Speed (Elevated)	0.3mph (0.48km/s)	
Gradeability	45%	
Outrigger Leveling (Side-to-side)	12° max.	
Outrigger Leveling (Front-to-rear)	7° max.	
Raise/Lower Time	63 / 58 seconds	80 / 70 seconds
Inside Turning Radius	6' 8" (2.03m)	
Outside Turning Radius	17' 4" (5.28m)	
Tires (Foam-filled)	355/55D625	
Controls	Proportional joystick	
Drive System	4WD – hydraulic	

POWER


Power Source

61hp Kubota V2403 diesel -or-55hp Kubota WG2503 Dual-fuel


WEIGHT Weight


26,420 lbs (11,984kg) 28,340 lbs (12,855kg)

TURNING RADIUS



S9056RT-HC S9070RT-HC





STANDARD FEATURES

- 4-wheel drive
- (4) Hydraulic outriggers w/ auto-leveling
- Dual powered extension decks
- Foam-filled tires
- Proportional controls
- Power line to platform
- Platform overload system
- Fold-down guardrails
- Flashing amber strobes (x2)
- Locking oscillating axle
- Hour meter & on-board diagnostics display
- Manual lowering valve
- Lanyard attachment points
- 2-year parts & labor warranty
- 5-year structural warranty

OPTIONS

- Hydraulic generator 110V 2kW
- Nylon spreader pads (set of 4)
- Environmental hydraulic oil
- Non-marking foam-filled tires
- Special paint colors



P.O. Box 1160 St. Joseph, MO 64502-1160, USA Tel: 1 (785) 989-3000 Toll-Free: 1 (800) 255-0317 Email: sales.usa@snorkellifts.com

ANSI Specification Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. ©Snorkel 2025 Refer to appropriate Snorkel operators manual for detailed instructions on the proper use and maintenance