

TB120/TB126J

TELESCOPING BOOM LIFTS



- Reliable & robust diesel telescoping boom lifts
- Powerful 4-wheel drive
- Simple to operate and maintain
- Available with or without jib
- Designed for construction applications

 **snorkel**[™]
www.snorkellifts.com

TELESCOPING BOOM LIFTS


DIMENSIONS	TB120	TB126J
Max. Working Height (A)	126' (38.40m)	132' (40.23m)
Max. Platform Height	120' (36.57m)	126' (38.40m)
Max. Horizontal Reach	62' (18.90m)	62' 11" (19.17m)
Platform Size	8' x 3' (2.44m x 0.91m)	
Overall Length (B)	42' 3" (12.88m)	44' 9" (13.64m)
Overall Width (C)	8' 6" (2.59m)	
Overall Width (Axles extended)	12' 9" (3.88m)	
Stowed Height (D)	9' 10" (3.00m)	10' 5" (3.17m)
Ground Clearance	13" (330mm)	

PERFORMANCE		
Platform Capacity	500 lbs (226kg)	
Max. Drive Height	80' (24.38m)	86' (26.21m)
Max. Wind Speed	28mph (12.5m/s)	
Max. Drive Speed (Stowed)	2.9mph (4.67km/h)	
Max. Drive Speed (Elevated)	0.15mph (0.24km/h)	
Gradeability	30%	
Jib Length	n/a	6' 6" (1.98m)
Jib Arc	n/a	135° (+70°/-65°)
Platform Rotation	150°	180°
Superstructure Rotation	360° continuous	
Tailswing (Axles retracted)	80.5" (2.04m)	
Tailswing (Axles extended)	54.25" (1.38m)	
Inside Turning Radius (Axles retracted)	19' (5.79m)	
Outside Turning Radius	33' (10.06m)	
Raise / Lower Time	208 / 215 seconds	
Tires (Foam-filled)	445-65 D22.5 (44.5cm x 114.9cm)	
Controls	Proportional joystick	
Drive System	4WD	


POWER		
Power Source	65hp Kubota V2403 diesel engine	

WEIGHT		
Weight	39,500 lbs (17,917kg)	41,800 lbs (18,960kg)

WORKING ENVELOPE



TB120/TB126J



STANDARD FEATURES

- Snorkel Guard™ secondary guarding system
- Hydraulic platform rotation
- 360° continuous turntable rotation
- 6' 6" 135° jib (TB126J)
- 4-wheel drive, braking & fixed front steer
- Proportional drive, lift, swing, extend & jib (if equipped)
- Built in jack for raising chassis
- Hydraulic extended rear axles w/ boom interlocks
- Power line to platform
- Tilt alarm & cut out
- Lanyard attachment points
- Foam-filled tires
- Flashing amber strobe
- 2-year parts & labor warranty
- 5-year structural warranty

OPTIONS

- AC generator 110V/2.5kW (single-phase)
- Airline to platform
- Environmental hydraulic oil
- Non-marking tires
- Special paint colors
- Tool tray

snorkel

www.snorkellifts.com

P.O. Box 1160
St. Joseph, MO 64502-1160, USA
Tel: 1 (785) 989-3000
Toll-Free: 1 (800) 255-0317
Email: sales.usa@snorkellifts.com