S3219 PLUS

LITHIUM ELECTRIC SLAB SCISSOR LIFT





- Self-propelled electric scissor lifts
- Low-level entry
- No hydraulic hoses
- Suitable for indoor/outdoor use
- Drives through a standard doorway
- Easy to use and maintain



LITHIUM ELECTRIC SLAB SCISSOR LIFT

S3219 PLUS


DIMENSIONS	
Max. Working Height	25' (7.62m)
Max. Platform Height (A)	19' (5.79m)
Platform Size (Stowed)	31.5" x 69" (80cm x 1.75m)
Platform Size (Extended)	31.5" x 105" (80cm x 2.67m)
Deck Extension Length	36" (91.4cm)
Overall Length (B)	72" (1.83m)
Stowed Height (C)	77.9" (1.98)
Overall Width (D)	32" (81.3cm)
Ground Clearance (Stowed)	2.63" (67mm)


PERFORMANCE	
Platform Capacity	600 lbs (272kg)
Max. Drive Height	19' (5.79m)
Max. Wind Speed	28 mph (12.5m/s)
Max. Drive Speed (Stowed)	2.0 mph (3.2m/s)
Max. Drive Speed (Elevated)	0.4 mph (0.6m/s)
Gradeability	25%
Raise/Lower Time	40 / 22 seconds
Inside Turning Radius	5" (127mm)
Outside Turning Radius	58" (1.47m)
Tires (Non-marking solid rubber)	12.7" x 4" (32.3cm x 10.2cm)
Controls	Proportional
Drive System	2WD – electric (24V)

POWER	
Power Source	(2) 24V 60Ah Lithium batteries
Charger	100–240VAC; 50–60Hz, 25amp

WEIGHT	
Weight	2,900 lbs (1,315kg)

TURNING RADIUS





STANDARD FEATURES

- Fully electric drive
- Fully electric steer
- No hydraulic hoses
- Roll-out deck extension w/ dual locks
- Non-marking tires
- Spill containment tray
- Swing-out service trays
- Single-gate entry
- Operates at full height indoor & outdoor
- Descent and all-motion alarms
- Flashing amber strobe
- Proportional control, including descent
- Platform overload system
- Power to platform
- On-board diagnostics, hour meter, battery meter
- Integrated battery charger
- Crane & forklift pockets
- Lanyard attachment points
- 2,000 charging cycles / 5-year** lithium battery warranty
- 2-year parts & labor warranty
- 5-year structural warranty

OPTIONAL FEATURES

- Environmental hydraulic oil
- Special paint colors
- Safety zone lights
- Slab scissor step



P.O. Box 1160

St. Joseph, MO 64502-1160, USA

Tel: 1 (785) 989-3000 Toll-Free: 1 (800) 255-0317

Email: sales.usa@snorkellifts.com